

QL-240

- Entry Level Wide Format Label Printer
- Print Labels 2" – 8.8" Wide



*Photo shows printer with optional touchscreen monitor.

Making Color Printing Affordable

The QL-240 is a cost effective, wide format, tabletop color label production system ideally suited for label printing within the facilities of brand owners, print shops or manufacturers. It is a great starter printer for those who want to start printing their own labels or introduce inkjet label technology for reducing costs of ribbon, print head and service. The QL-240 is a smart alternative to expensive, pre-printed labels and thermal transfer labels, allowing for production color labels instead of one-color or black & white labels.

Designed with the user in mind, the QL-240 optimizes LEAN processes by creating smooth and flexible production in-house with its user friendly interface. A versatile system for almost any market, the printer's fast speed allows users to reduce inventory and quickly produce vibrant high resolution labels on a just-in-time basis.

- **Fast print speed up to 12 inches per second (60 ft per minute)**
- **Superior print resolution up to 1600 dpi**
- **Print width 2" to 8.8"**
- **Ideal introductory in-house label production system**
- **Great solution for private labelers and business owners**





*Photo shows printer with special options.

QL-240 Specifications

Operation:

Ink Type:	Dye ink, (5) individual CMYKK color ink cartridges
Print Resolution:	Up to 1600 x 1600 dpi
Print Speed:	6 ips (152 mm/sec) or 12 ips (305 mm/sec)
Print Area:	Width: 2" (51 mm) – 8.8" (223 mm) Length: 1" (25 mm) – 30" (762 mm)
Media Sensors:	Gap, Reflective (bottom-only), Continuous; Non-adjustable/fixed sensors
Connectivity:	10/100 BaseT Ethernet, RJ-45 connection
Software:	Microsoft Windows® 10, 8.1, 8, 7; Windows Server® 2012, 2008, 64/32-bit Drivers, Touchscreen Monitor (optional), NiceLabel® software (optional)

Printing Supplies:

Ink Cartridges:	QuickLabel® QL-240 CMYKK dye cartridges, 250 mL each
Maintenance Cartridge:	Maintenance tray with replaceable modules
Ink Type:	High performance, water-based dye inks with extra wide color gamut that produce true- to-life color when combined with QuickLabel approved media.

Media Dimensions:

Width:	2" (51 mm) – 9.5" (241 mm)
Length:	1" (25 mm) – 30" (762 mm)
Thickness:	4.0 mil (0.102 mm) - 12 mil (0.305 mm)
Roll Size:	9.8" OD (250 mm) QuickLabel paper and synthetic labels on 3" ID (76 mm) core
Types:	Paper, Inkjet coated gloss paper, PE, PET, PP

Environmental & Physical:

Printer Operating:	41° F to 95° F (5° C to 35° C), 20% to 90% Relative Humidity (non-condensing). Printer should be installed on level surface with no more than 1° tilt in any axis.
Power Requirements:	100-240 VAC 50-60 Hz, 2.6A
Power Consumption:	Operating: 260W (max) Idle: 60W (max)
Dimensions:	Printer: 18.9" x 15.6" x 11.9" (480 mm x 395 mm x 301 mm) Unwinder: 19.7" x 19.7" x 16.8" (500 mm x 500 mm x 427 mm)
Weight:	Printer and Screen: 97 lbs. (44 Kg)
Optional Accessories:	Automatic Label Roll Rewinder and Premium Unwinder, Touchscreen Monitor

Warranty:

Printer: 12 Month Manufacturer's Parts & Labor Warranty (excludes wear parts and supplies)



QuickLabel
Toll-free: 877-757-7978
Tel: +1 401-828-4000
info@quicklabel.com
www.quicklabel.com